

INPUT	
Rated power	60000 VA
Voltage	400 V three-phase
Voltage tolerance	400 ±20% @ full load
Frequency	50 o 60 Hz with autorange
Frequency tolerance	45 - 65 Hz
Power factor	>0.93
Current distortion	<6%
Soft start	0 - 100% in 120 sec. configurable

BY PASS	
Rated voltage	380 / 400 / 415 three-phase
Voltage tolerance	±15% (selectable from ±10% to ±25% from front panel)
Rated frequency	50 o 60 Hz (autorange)
Frequency tolerance	±2% (selectable from ±1% to ±5% from front panel)
Number phases	3
Back-feed protection	yes
Overload capacity Inx10ms	14

OUTPUT and INVERTER OUTPUT	
Rated power	60000 VA
Active power	48000 W
Number phases	3 + N
Crest factor (Ipeak/Irms)	3 : 1
Waveform	Sinewave
Static stability	±1%
Dynamic stability	±5%
Frequency	50 o 60 (configurable)
Voltage distortion with non-linear load	<3%
Voltage distortion with linear load	1% (typical), 2% max.
Frequency stability	±2% (selectable from ±1% to ±5% from front panel)
Inverter efficiency at rated load	91% %
Overload	110% for 60 min.; 125% for 10 min.; 150% for 1 min.

RECTIFIER OUTPUT	
Ripple	<1%

BATTERIES	
Type	Maintenance-free sealed lead-acid
Maximum recharge current	0.2xC10

ENVIRONMENTAL	
Altitude max	1000 m
Color	Light grey RAL 7035
Remote controls	ESD and bypass
Protection rating	IP20
Cooling (type)	Redundant fans (front-top)
AC/AC efficiency	92.5%
Noise (at 1 m)	68 - 70
Remote signals	dry contacts
Operating temperature	0 ÷ 40 °C
Relative humidity	5-95% non-condensing
Standards	European directives: L V 2014/35/EU low voltage; EMC 2014/30/EU electromagnetic compatibility -- Directive and Standards: Safety IEC EN 62040-1; EMC IEC EN 62040-2; RoHS compliant -- Classification in accordance with IEC 62040-3 VFI - SS - 111

Master Industrial
MIM 60



DATA	
Weight	910 kg
Dimensions (h w d)	1900x1200x800 mm