

INPUT	
Rated power	800000 VA
Voltage	380 / 400 / 415 V three-phase
Voltage tolerance	400 V $\pm 20\%$ @ full load
Frequency	40 - 70 Hz
Power factor	0.99
Current distortion	<3%
Soft start	0 - 100% in 120 sec. (selectable)

BY PASS	
Rated voltage	380 / 400 / 415 V three-phase + N
Voltage tolerance	$\pm 20\%$ (selectable from $\pm 5\%$ to $\pm 25\%$ )
Rated frequency	50 or 60 Hz (selectable)
Frequency tolerance	$\pm 2\%$ (selectable from $\pm 1\%$ to $\pm 5\%$ )
Rated current	1155 A
Back-feed protection	yes
Overload capacity $I_{n \times 10ms}$	11

OUTPUT and INVERTER OUTPUT	
Rated power	800000 VA
Active power	800000 W
Output Voltage	380 / 400 / 415 V three-phase + N (selectable)
Waveform	Sinewave
Static stability	$\pm 1\%$
Dynamic stability	$\pm 5\%$ in 10 msec.
Frequency	50 or 60 Hz (selectable)
Voltage distortion with non-linear load	<3%
Voltage distortion with linear load	<1%
Overload	110% for 60 minutes, 125% for 10 minutes, 150% for 1 minute
Short-circuit current	2.7 $I_n$ for 100 msec, + 2.0 $I_n$ for 900 msec.
AC Voltage Regulation: Battery Mode	$\pm 1\%$
Frequency Range: Synchronized	$\pm 2\%$ selectable

RECTIFIER OUTPUT	
Ripple	0

BATTERIES	
Type	VRLA AGM / GEL, NiCd, Supercaps, Li-ion, Flywheels
Maximum recharge current	-0.11% x V x °C

ENVIRONMENTAL	
Color	Dark grey RAL 7016
Remote controls	EPO, bypass battery charge block (configurable)
Communication	USB + Dry contacts + 2 slots for communications interface
Safety compliance	EN 62040-1:2019; EN 62040-1/AC:2019;
EMC compliance	EN 62040-2:2018
Protection rating	IP20 (other on request)
Cooling (type)	Forced air via speed controlled internal fans
AC/AC efficiency	up to 97% (ON LINE Mode)
Noise (at 1 m)	68 [dBA] (50% load), 74 [dBA] (100% load)
Operating temperature	0 °C - +40 °C
Relative humidity	5-95% non-condensing

DATA	
Weight	1985 kg
Dimensions (h w d)	2400x1900x850 mm